



# *VoIP Intercom Module Configuration Guide*

NQ-GA10P, NQ-GA10PV

**BOGEN®**

© 2021 Bogen Communications LLC  
All rights reserved.  
740-00068C  
230420

# Contents

- Configuring the Nyquist VoIP Intercom Module ..... 1**
  - Using the Dashboard .....3
  - Standalone Operation .....4
  - Updating Firmware .....5
  - Network Settings Tab Parameters .....7
  - Configuration Settings Tab Parameters .....10
    - Standalone Operation Configuration Settings .....12
  - Accessing Log Files .....16
- Appendix A: Bogen Digital Certification Authority ..... 19**
  - Installing the Bogen Digital Certification Authority .....19
    - Installing Certification Authority on Windows System .....19
    - Installing Certification Authority on Mac System.....20
    - Installing Certification Authority on an Android Device .....21
    - Installing Certification Authority on an iOS Device .....21
    - Viewing the Certificate .....21

# Configuring the Nyquist VoIP Intercom Module

Bogen's plenum-rated Nyquist Voice over Internet Protocol (VoIP) intercom modules transform any low-impedance analog speaker into a full-featured Power-over-Ethernet (PoE) IP speaker. The modules use the latest technology to deliver superior audio quality, making them perfect for IP paging and audio distribution. The built-in talkback capability allows these modules to be used in VoIP intercom applications.

These 10W single-channel intercom modules are available with (NQ-GA10PV) or without (NQ-GA10P) an HDMI video output, depending upon the application needs. They also offer a CAN bus interface to work with the NQ-E7020 Digital Call Switch and a Form-C relay for controlling third-party devices (e.g., A/V override).

When paired with Bogen's ANS500M microphone module (optional), these intercom modules can be turned into an ambient noise sensor to help maintain paging and background music intelligibility in high-noise environments. Alternatively, it can be paired with the Bogen DDU250 Dynamic Desktop Microphone and configured as a push-to-talk microphone station, allowing it to perform a preconfigured zone page or All-Call page (including Emergency and Multi-Site).

If an HDMI video device is attached, this device can display messages and images sent by a Nyquist server, as well as a digital or analog clock. These messages can be used for scheduled announcements, emergency instructions, automatically triggered messages, simple ad-hoc messages, or many other purposes. If a Nyquist server is not present, the device will display an analog clock. For further information on displaying and scheduling messages, see the *"Managing GA10PV Display Messages"* section of the *Nyquist System Administrator Guide*.

The Nyquist server or System Controller can automatically discover and configure the VoIP intercom module, but you can also manage the device, and manually configure some settings, through the VoIP Intercom Module's web-based user interface (web UI).

A two-second press of the appliance's **Reset** button reboots the device. If you press the **Reset** button for 10 seconds, the appliance returns to the factory default configuration settings. Returning to the default configuration settings does not change the appliance's firmware.

The following sections describe the process for manual configuration. For information about using Nyquist's automatic configuration process, refer to the appropriate *Nyquist System Administrator Guide*.

---

*Note:* Do not use third-party Chrome browser extensions with the Nyquist user interface.


---

To access the appliance's Web-based user interface (UI):

- 1 Before accessing the web UI for the first time, the Bogen Certification Authority (CA) digital certificate must be installed on the client. This certificate can be downloaded from any Nyquist appliance and enables your browser to recognize the Nyquist web application as a trusted site.

For details on how to download and install the certificate to your client computers, see *"Installing the Bogen Digital Certification Authority" on page 19*.

- 2 Access the appliance's web UI by doing one of the following:
  - a) On your web browser, enter the IP address for the appliance as the URL.
  - b) From the Nyquist server's web UI navigation bar, select **Stations**, select **Stations Status** or **Appliance Status**, navigate to the device that you want to configure, and then select the **Link** icon.



**Figure 1. Nyquist Appliance Login**

- 3 At the Nyquist appliance's Login page, enter username and password, then press enter or click on the **Login** button.


The default username is **admin**; the default password is **bogen**.

---

*Note:* After a successful login, a warning will be displayed if the default password is still in use. We strongly encourage changing the default password as soon as possible.

---

When you have logged in successfully, you will be presented with the dashboard for the appliance.



**Figure 2. Intercom Module Dashboard**

## Using the Dashboard

The dashboard displays the following fields:

**Table 1. Appliance Dashboard Fields**

<b>Device Type</b>	Identifies the model of this device.
<b>Serial Number</b>	Identifies the serial number for the device.
<b>MAC Address</b>	Identifies the Media Access Control (MAC) address, which is a unique identifier assigned to network interfaces for communications on the physical network segment.
<b>Firmware Version</b>	Identifies the firmware version installed on the device.
<b>Relay Trigger Status</b>	When enabled in Configuration Settings, this field indicates the status of the NO/NC output relay, which is activated whenever an audio signal is being sent to the speaker output.
<b>Standalone Operation</b>	Enables or disables Standalone mode.

The following buttons are available at the top of all pages in the application.

**Table 2. Appliance Dashboard Buttons**

<b>Dashboard</b>	Displays the dashboard.
<b>Configuration Settings</b>	Accesses the Configuration Settings page where you can view and set various options. If Standalone Operation is not enabled, you can also receive configuration settings from a Nyquist server.
<b>Network Settings</b>	Accesses the Network Settings page where you can view and set network settings, such as the static IP address.
<b>Firmware Update</b>	Accesses the Firmware Update page where you can view the current Nyquist version, update firmware to a new version, restore the configuration to factory defaults, and reboot the appliance.
<b>Logs</b>	Accesses log files, which record either events or messages that occur when software runs and are used when troubleshooting the appliance.
<b>Help</b>	Accesses the appliance's online help.
<b>Manual</b>	Displays this appliance's configuration guide.
<b>Logout</b>	Logs out of the appliance's web UI.

## Standalone Operation

This device can also run in Standalone Operation mode, where it will not interact with a Nyquist server (e.g., E7000 or C4000). This means the device will not:

- Fetch device configuration from Nyquist server
- Register with Nyquist server (via SIP)
- Store backup information to Nyquist server
- Allow access to Nyquist server-based NTP
- Display messages or images from the Nyquist server

Standalone Operation allows this device to be used without a Nyquist server as a generic SIP endpoint when integrated with a 3<sup>rd</sup>-party VoIP telephone system or other SIP server-based solutions, such as a unified communications (UC) platform. In a non-SIP environment, these devices are capable of receiving audio through one or more prioritized multicast channels.

# Updating Firmware

When you select **Firmware Update** from the appliance's web UI, the Firmware Update page appears. From this page you can determine which Nyquist firmware version the appliance is using and if an update is available. You can also load a firmware release, install the loaded firmware, restore the configuration to factory defaults, and reboot the appliance.

---

*Note:* A Nyquist appliance connected to the Nyquist network receives a configuration file from the Nyquist server that includes the latest firmware available from the server. If the firmware is different from the one installed on the appliance, an automatic firmware update occurs unless the **Firmware** parameter for the station is left blank. Refer to the *Nyquist System Administrator Guide* for more information.

---



*Note:* Some buttons only appear on this page when applicable.

**Figure 3. Firmware Update Page**

*To use the Firmware Update page:*

- 1 On the appliance web UI's main page, select **Firmware Update** to view or update the firmware version.
  - If the device is in Standalone mode, the **Check for Updates** button will be shown. Selecting it checks the Bogen website for the latest firmware version available. If a

version newer than the one currently installed is found, it is downloaded to the appliance and the **Update Firmware** button will be shown.

- If you already have a firmware file you would like to install to the appliance, select **Upload Firmware** to upload the firmware file from your computer to the appliance. A popup screen appears that allows you to select the file that you want to upload. You can navigate to the file's location. After you select the file, select **Upload**.

The page displays the uploaded firmware version ("New Nyquist Version") and an **Update Firmware** button appears. Select this button if you want to update the appliance's firmware to the uploaded version.

- If you want to return your appliance to its original factory configuration, select **Restore Factory Settings**.
- Select **Reboot Appliance** to restart your appliance.

**Table 3. Firmware Update settings**

<b>Current Nyquist Version</b>	Shows the version of the appliance's currently installed firmware.
<b>New Nyquist Version</b>	Shows the version of the firmware that has been loaded, though not installed, onto the appliance.
<b>Update Firmware</b>	<p>Available only when a new firmware version has been loaded onto the appliance (as specified in New Nyquist Version).</p> <p>Installs the loaded firmware. A reboot may be required after installation.</p>
<b>Upload Firmware</b>	<p>Prompts the user to specify a firmware file, which will then be loaded (though not installed) onto the appliance.</p> <p><i>Note:</i> To obtain the firmware file for a specific version, please contact Bogen Technical Support.</p>
<b>Check for Updates</b>	<p>Available only when the appliance is configured for Standalone mode.</p> <p>Checks the Bogen website for the latest firmware version available and, if it finds a version newer than what is currently installed, downloads it to the appliance.</p> <p><i>Note:</i> Ensure your Nyquist appliance has network access to <a href="http://bogen-ssu.bogen.com">bogen-ssu.bogen.com</a>, port 22.</p>

**Table 3. Firmware Update settings**



<b>Restore Factory Settings</b>	Returns the appliance to its original factory configuration.  <i>Note:</i> This does not install the original appliance firmware. The firmware will not be changed.
<b>Reboot Appliance</b>	Restarts the appliance.

## Network Settings Tab Parameters

Network settings can be configured dynamically by the Nyquist server or manually by using the appliance's web UI.

*To manually configure network settings:*

- 1 On the appliance web UI's main page, select **Network Settings**.
- 2 Select your desired network settings.
- 3 Select **Save**.


**Network Settings**


IP Address:

172.31.19.220

Netmask:

255.255.255.0

Gateway:

172.31.19.254

VLAN ID:

9

VLAN Priority:

0 - Best Effort ▼

NTP Server:

172.31.19.203

TFTP Server:

172.31.19.203

TFTP Server from DHCP


No ▼

DHCP Enabled:

Yes ▼

Reboot Appliance:

No ▼

 Save

**Figure 4. Network Settings**

Network settings are described in the following table:

**Table 4. Network Settings**

<b>IP Address</b>	Identifies the IP address assigned to the appliance.
<b>Netmask</b>	Identifies the subnetwork subdivision of an IP network.
<b>Gateway</b>	Identifies the address, or route, for the default gateway.
<b>VLAN ID</b>	Identifies the Virtual Local Area Network (VLAN) for this appliance. Values range from 0 to 4094.
<b>VLAN Priority</b>	Identifies the priority of the network traffic on the VLAN. Priority can range from 0 through 7.

**Table 4. Network Settings (Continued)**

<b>NTP Server</b>	<p>Identifies the IP address or the domain name of the Network Time Protocol (NTP) Server.</p> <p><i>Note:</i> This field is only editable when Standalone Operation is enabled.</p>
<b>TFTP Server</b>	<p>Identifies the host name or IP address of the Trivial File Transfer Protocol (TFTP) server.</p> <p>The specified TFTP server can be used to automatically set this device's <b>Configuration</b> settings via the <b>Get Configuration from Server</b> button.</p> <p>If <b>TFTP Server from DHCP</b> (see below) is set to "Yes", this value will be auto-configured via DHCP option 66, assuming the DHCP server has been configured to provide option 66. For details, see the documentation for your DHCP server.</p> <p><i>Note:</i> A TFTP server runs on the Nyquist server on port 69 (the standard TFTP port) and the optional Nyquist DHCP service automatically provides this TFTP address via option 66.</p> <p><i>Note:</i> If this value is unspecified, the <b>TFTP Server from DHCP</b> will automatically be set to "Yes", this field will become read-only, and DHCP will be used to configure this setting. To change this value, the <b>TFTP Server from DHCP</b> setting must be set to No, which makes the field editable.</p> <p><i>Note:</i> This setting is not available when Standalone Operation is enabled.</p>
<b>TFTP Server from DHCP</b>	<p>"Yes" means the device will use the DHCP option 66 value to retrieve an address for the TFTP Server from DHCP.</p> <p>"No" means the device will ignore the DHCP option 66 value and use the manually configured value of the TFTP Server (see above).</p> <p><i>Note:</i> This setting is not available when Standalone Operation is enabled.</p>
<b>DHCP Enabled</b>	<p>Indicates if the device is enabled to use DHCP to retrieve its IP configuration.</p>
<b>Reboot Appliance</b>	<p>Indicates that this appliance should reboot when the Save button is clicked.</p>

# Configuration Settings Tab Parameters

The easiest way to configure Nyquist appliances is to obtain configuration settings from the Nyquist server by selecting **Get Configuration From Server**. However, you can manually configure an appliance through the appliance's Web UI when Standalone Operation is enabled (see "*Standalone Operation Configuration Settings*" on page 12).

To view or modify the Nyquist appliance configuration:

- 1 On the appliance Web UI's main page, select **Configuration Settings**.
- 2 View the settings as described in Table 5 on page 11 for normal configuration, or modify the settings as described in "*Standalone Operation Configuration Settings*" on page 12 for Standalone Operation configuration.
- 3 If changes were made (Standalone Operation only), click the **Save Configuration Settings** and/or **Save Multicast Addresses** buttons to save your changes.

### Configuration Settings

[Get Configuration From Server](#)

Web Username:

	IP Address	Port Number	Cut Level	Station List
Emergency-All-Call:	<input type="text" value="239.0.2.1"/>	<input type="text" value="62001"/>	<input type="text" value="-16"/>	<input type="text" value="1"/>
All-Call:	<input type="text" value="239.0.2.2"/>	<input type="text" value="62002"/>	<input type="text" value="-17"/>	<input type="text" value="1"/>
Audio Distribution:	<input type="text" value="239.0.2.3"/>	<input type="text" value="62003"/>	<input type="text" value="-28"/>	<input type="text" value="1"/>
Multicast 1:	<input type="text" value="239.0.2.11"/>	<input type="text" value="63746"/>	<input type="text" value="-10"/>	<input type="text" value="1"/>
Multicast 2:	<input type="text" value="239.0.2.10"/>	<input type="text" value="62010"/>	<input type="text" value="-21"/>	<input type="text" value="1"/>

**Nyquist Control Password**

[Save Password](#)

**Device Stations**

Port Number	Port Type	Account Id	Local Port	Username
<input type="text" value="1"/>	<input type="text" value="Speaker-Only"/>	<input type="text" value="sip:112@172.31.19.203"/>	<input type="text" value="5060"/>	<input type="text" value="112"/>

The following table describes the **Configuration Settings** tab settings when Standalone Operation is *not* enabled for this device:

**Table 5. Configuration Settings (Standalone disabled)**

<b>Get Configuration from Server</b>	Retrieves configuration settings (i.e., web username, server, and local port) from the TFTP server specified in the Network Settings (see Table 1 on page 1).
<b>Web Username</b>	Displays the username of the current user.
<b>Emergency-All-Call</b>	Identifies the IP address, port number, cut level (volume), and station list used for emergency all-call pages.
<b>All-Call</b>	Identifies the IP address, port number, cut level (volume), and station list used for all-call pages.
<b>Audio Distribution</b>	Identifies the IP address, port number, cut level (volume), and station list used for audio distribution.
<b>Multicast #</b>	Identifies the IP address, port number, cut level (volume), and station list used for the multicast audio stream of one (or more) zones.
<b>Nyquist Control Password</b>	<p>Specifies a password used to secure Nyquist control messages between this device and the Nyquist server. This value must match the password specified on the Nyquist server to support certain Nyquist features, such as sound masking, amp protection mode, and station check-in.</p> <p>The specified password must be exactly 20 characters long and include uppercase, lowercase, and numeric characters.</p> <p><i>Note:</i> This password cannot be set unless the Web Password has been changed from the default value.</p>

The **Configuration Settings** tab also displays the following information for each **Device Station** attached to the amplifier:

<b>Port Number</b>	Shows the port number of the appliance.
<b>Port Type</b>	Shows the station type to which the port connects.
<b>Account ID</b>	Shows the SIP account (IP address) associated with the device preceded by the extension of the device associated with this port.

<b>Local Port</b>	Shows the port used for SIP.
<b>Username</b>	Shows the username or extension for the station associated with the port.

## Standalone Operation Configuration Settings

Configuration Settings

Device Type:

NQ-GA10PV-Intercom HDMI Module

Device Name:

NQ-GA10PV

Web Username:

admin

Web Password:

Web Confirm Password:

Time Zone:

Select a time zone

Output Power (Watts):

1/2

Enable SIP Calls:

Yes

External Relay Trigger:

Disabled

SIP Server Address:

SIP Network Port:

SIP Codecs:

G722 ulaw alaw

SIP Extension:

SIP Username:

SIP Password:

Talkback Gain: -6 dB

Type:

Digital Call Switch & Speaker

Dial Extension:

Intercom Cut Level: -6 dB

Save Configuration Settings

Multicast Addresses (Receive)

Sorting:

Disabled

		Multicast IP Address	Multicast Port Number	Codec	Channels	Cut Level (dB)	Description
+		239.1.1.1	6000	G711 u-law	1	-20	Empty
+		239.1.1.1	6002	G711 u-law	1	-20	Empty

Note:

The following codecs are supported for multicast: G711 u-law, G711 a-law, G722, and OPUS.

Save Multicast Addresses (Receive)

**Figure 5. Appliance Configuration Settings (Standalone enabled)**

Configuring this device consists of specifying one or more of the following:

- The SIP server addresses, ports, and SIP extensions at which to register for incoming SIP pages and announcements.
- The input multicast addresses (and ports) from which the device will receive digital signals, which will then be converted to analog and played to the speaker output.

To use this device to make announcements or SIP calls, connect a Push-to-Talk (PTT) microphone to the speaker and call switch connections (refer to the *VoIP Intercom Module Installation and Use Guide*).

To receive announcements or SIP calls, configure one or more **Multicast Addresses** entries with the multicast addresses and ports from which to receive the input streams. Specify a codec, cut level, and output channel (i.e., speaker) on which to play the received (and decoded) audio signal.

The following table describes the **Configuration Settings** tab settings when Standalone Operation is enabled for this device:

**Table 6. Configuration Settings (Standalone enabled)**

<b>Device Type</b>	Displays the type of this device.
<b>Device Name</b>	Provides a name for this device.
<b>Web Username</b>	Specifies a web username for this appliance.
<b>Web Password</b>	Specifies a web password for logging into the appliance.
<b>Web Confirm Password</b>	Re-enter the password used to log into the appliance.
<b>Time Zone</b>	Specifies the time zone in which the device resides.
<b>Output Power (Watts)</b>	Specifies the output power for the amplifier in Watts. Valid values are: 1/8, 1/4, 1/2, 1, 2, 4, and 8.
<b>Enable SIP Calls</b>	Enables this device to receive one-way SIP calls, wherein only the caller can be heard (such as announcements). If enabled, a number of SIP-related configuration settings are displayed.
<b>External Relay Trigger</b>	<b>Enabled or Disabled</b>  Enables this device to apply a trigger signal to the external relay output to notify an external device that an output signal is being sent to speaker output.
<b>SIP Server Address<sup>a</sup></b>	Specifies the IP address of the SIP Registration Server with which the device will register.
<b>SIP Network Port<sup>a</sup></b>	Specifies the IP port on which to communicate with the SIP Registration Server (typically 5060).

**Table 6. Configuration Settings (Standalone enabled)**

<b>SIP Codecs<sup>a</sup></b>	Displays a read-only list of codecs allowed on SIP sessions.
<b>SIP Extension<sup>a</sup></b>	<p>Specifies the SIP extension for this device.</p> <p>The extension, along with the IP address, is used to specify the URI used to place a SIP call to this extension:</p> <p style="text-align: center;"><code>sip:&lt;extension&gt;@&lt;local_ip_address&gt;</code></p>
<b>SIP Username<sup>a</sup></b>	Specifies the SIP username used to register with the SIP server.
<b>SIP Password<sup>a</sup></b>	Specifies the SIP registration password used to register with the SIP server.
<b>Talkback Gain<sup>a</sup></b>	<p>Input gain applied to talkback for intercom calls.</p> <p>This can be a value from -12 to 20 dB.</p>
<b>Type<sup>a</sup></b>	<p>Specifies how the device will be used. Options are:</p> <ul style="list-style-type: none"><li>• VoIP Speaker Only</li><li>• Digital Call Switch &amp; Speaker</li></ul>
<b>Dial Extension<sup>a</sup></b>	Only available when <b>Type</b> is set to <b>Digital Call Switch &amp; Speaker</b> , this indicates which extension will be called when the call button is activated.
<b>Intercom Cut Level<sup>a</sup></b>	<p>Cut level for intercom calls.</p> <p>This can be a value from -42 to 0 dB.</p>

a. Available only when Enable SIP Calls has a value of Yes.

The following parameters appear for each Multicast Address configured for this device.

<b>Multicast IP Address</b>	Specifies the multicast IP address on which to receive audio streams.
<b>Multicast Port Number</b>	Specifies the multicast port on which to receive audio streams.

**Codec**

Specifies the codec to be used when decoding audio.  
Select one of the following values:

- G711 u-law
  - Intercom call quality
  - A narrowband audio codec that provides toll-quality audio at 64 kbps. The u-law version is primarily used in North America and Japan.
- G711 a-law
  - Intercom call quality
  - A narrowband audio codec that provides toll-quality audio at 64 kbps. The a-law version is primarily used in most countries outside of North America and Japan.
- G722
  - Tone and paging quality
  - A wideband audio codec operating at 48, 56, and 64 kbps.
- OPUS
  - Music quality
  - An audio codec format designed for speech and general audio, supporting low latency, constant and variable bitrate encoding (6 to 510 kbps), and five sampling rates (from 8 to 48 kHz).

**Channels**

Channel(s) on which the audio streams will be output.

- This is always **1**.

**Cut Level (dB)**

Specifies the cut level for the audio stream.

This can be a value from -70 to 0 dB.

The default value is -20 dB.

*Note:* To modify, click on the value, adjust the slider on the popup using the cursor keys or mouse, and click the check box button.

**Description**

User-specified description of this multicast address.

This setting can contain a maximum of 30 characters and should not contain any of the following: `[]{}<>,|:`

---

*Note:* A maximum of 24 multicast entries is supported.

---

---

*Note:* Multicast Addresses should be ordered by priority, highest priority first. If multiple streams are active on the same channel simultaneously, the one with the highest priority will be played. Set the **Sorting** switch to Enabled and drag entries using the 4-way arrow symbols to drag entries up and down to rearrange the priorities.


---

## Accessing Log Files

A log file records events and messages that occur when software runs, to be used when troubleshooting the appliance. From the appliance's web-based UI, log files can be viewed directly or exported via download to your PC, Mac, or Android device, where they can be copied to removable media or attached to an email for technical support.

*To view a log file:*

- 1 On the appliance Web UI's main page, select **Logs**.
- 2 From the drop-down menu, select the log that you want to view.  
Multiple versions of the same log, and zipped copies of the log, may be available.
- 3 To export the file, select **Export**.  
A link to a .txt file appears in the browser's lower left corner.



**Figure 6. Logs**

Available logs are described in the following table. If a log file is empty, however, it will not appear in the drop-down list of available logs.

**Table 7. Logs**

Log	Description
ampws.log	Contains information about protection status and logs protection events with temperature information at the time of event.
auth.log	Contains system authorization information, including user logins and authentication methods that were used.
btmtp	Contains information about failed login attempts.
daemon.log	Contains information logged by the various background daemons that run on the system.
debug	Contains errors and debug information.
dpkg.log	Contains information that is logged when a package is installed or removed using dpkg command.
faillog	Contains user failed login attempts.

**Table 7. Logs (Continued)**

<b>Log</b>	<b>Description</b>
kern.log	Contains information logged by the kernel and recent login information for all users.
lastlog	Contains information on the last login of each user.
messages	Contains messages generated by Nyquist.
php5-fpm.log	Contains errors generated by the PHP script.
syslog	Contains list of errors that occur when the server is running and server start and stop records
user.log	Contains information about all user level logs.

# Appendix A: Bogen Digital Certification Authority

## Installing the Bogen Digital Certification Authority

When your client (e.g., a web browser) connects to the Bogen device's web application, the device's digital certificate is sent to the client to authenticate the identity of the device's web application. The client uses the Bogen Certification Authority (CA) certificate to authenticate the device's digital certificate, which verifies that the client is connecting to a valid server. If you do not install the Bogen CA certificate, the browser will display a warning that it was unable to authenticate the server, displaying a red *Not secure* warning immediately to the left of the browser's address bar when you attempt to access the Bogen device.

### Installing Certification Authority on Windows System

*To download and install the Certification Authority on a Windows device:*

- 1 From your Chrome or Edge browser, type `http://<device>/ssl/bogenCA.crt` in the address bar, where `<device>` is the Nyquist device's IP address or DNS name (for example, `http://192.168.1.0/ssl/bogenCA.crt`).
- 2 Select the downloaded file and select **Open**.
- 3 Select **Open** when prompted with "Do you want to open this file?"
- 4 Select the **Install Certificate...** button. The Certificate Import Wizard starts.
- 5 Select **Current User**, and then select **Next**.

---

*Note:* To allow *all* users on this Windows client to access the Nyquist device, select **Local Machine** instead of **Current User**. You may be prompted for administrator credentials.

---

- 6 Select "Place all certificates in the following store", then select **Browse**.
- 7 Select **Trusted Root Certification Authorities**, and then select **OK**.
- 8 Select **Next**.
- 9 Select **Finish**.
- 10 Restart the browser and log in to the device's web application.

You can also download and install the Certification Authority using a PowerShell command prompt or script, which involves fewer steps.

To download the certificate to a CRT file, execute the following PowerShell command, replacing `<device>` with the IP address or DNS name of the Nyquist device:

```
Invoke-WebRequest -Uri http://<device>/ssl/bogenCA.crt -OutFile  
$env:TEMP\bogenCA.crt
```

If you wish to validate the certificate before importing it, execute the following command after retrieving the CRT file:

```
(New-Object -TypeName Security.Cryptography.X509Certificates.X509Certificate2 -ArgumentList "$env:temp\bogenCA.crt").GetCertHashString()
```

The output will be the hash value (i.e., thumbprint) of the downloaded certificate, which should match the following (as of the current release):

```
0A8248F69D970F8DD855D0E0592972DA64B1A845
```

To install the certificate for the current user, execute the following command:

```
Import-Certificate -CertStoreLocation cert:\CurrentUser\Root -FilePath  
$env:TEMP\bogenCA.crt
```

That command installs the CA certificate into the CurrentUser certificate store, which only applies to the current user. To install the certificate for all users on this machine, which requires administrator privileges to execute, execute the following command:

```
Import-Certificate -CertStoreLocation cert:\LocalMachine\Root -FilePath  
$env:TEMP\bogenCA.crt
```

*Note:* These commands can also be executed remotely using PowerShell Remoting, which may be helpful if the certificate needs to be installed on many client machines.

## Installing Certification Authority on Mac System

*To download and install the Certification Authority on a Mac:*

- 1 From your Chrome or Edge browser, type `http://<device>/ssl/bogenCA.crt` in the address bar, where `<device>` is the Nyquist system device's IP address or DNS name (for example, `http://192.168.1.0/ssl/bogenCA.crt`).
- 2 Save the downloaded `bogenCA.crt` file to the desktop.
- 3 Double-click the certificate file on the desktop.  
The Keychain Access App opens.
- 4 Double-click the certificate to reveal the trust settings.
- 5 Change the top trust setting to **Always Trust**.
- 6 Close the Trust Setting window and enter the computer administrative password to save.
- 7 Restart the browser and log in to the Nyquist web application.

## Installing Certification Authority on an Android Device

---

*Note:* The Android device WiFi must be connected to the same network as the Nyquist Server.

---

*To download and install the Certification Authority on an Android device:*

- 1 From your Chrome or Edge browser, type `http://<device>/ssl/bogenCA.crt` in the address bar, where `<device>` is the Nyquist device's IP address or DNS name (for example, `http://192.168.1.0/ssl/bogenCA.crt`).
- 2 If prompted, verify your identity (e.g., enter your PIN or fingerprint).
- 3 Type a certificate name (e.g., "Bogen CA"), specify "VPN and apps" under "Used for", and select **OK** to install the certificate.

## Installing Certification Authority on an iOS Device

---

*Note:* The iOS device WiFi must be connected to the same network as the Nyquist Server.

---

*To download and install the Certification Authority on an iPhone Operating System (iOS) device:*

- 1 From your Safari browser, type `http://<device>/ssl/bogenCA.crt` in the address bar, where `<device>` is the Nyquist device's IP address (for example, `http://192.168.1.0/ssl/bogenCA.crt`).
- 2 Select **Go**.
- 3 Select **Allow** when prompted to allow the download.
- 4 Select **Close** after the notification that a profile was downloaded.
- 5 Select **Settings > General > VPN & Device Management**.
- 6 Select the **Bogen CA** certificate under **DOWNLOADED PROFILE**.
- 7 Select **Install**.
- 8 If prompted, enter your passcode.
- 9 On the **Warning** page, select **Install**.
- 10 Select **Done**.
- 11 Select **Settings > General > About > Certificate Trust Settings**.
- 12 Under **ENABLE FULL TRUST FOR ROOT CERTIFICATES**, Enable the switch next to **Bogen CA**.

## Viewing the Certificate

The following steps outline how to view and verify the TLS/SSL certificate that was provided by the Nyquist device.

---

**Important:** The user interfaces for browsers change not infrequently, so the exact details may vary from what is described in the following instructions. Some security packages can also affect the information available, such as antivirus software that injects its own CA certificate in lieu of the website's actual certificate, which has the effect of hiding the actual certificate from the user.

---

- 1 Browse to the Bogen device's web application in your browser (using Safari on iOS, Chrome or Edge on all other platforms).
- 2 Select the lock icon on the address bar of the browser (to the left of the URL).
- 3 Display the CA certificate by following one of the following steps:
  - a) On the Chrome or Edge browser, select **Connection is secure**, then select either **Certificate is valid**, the certificate icon, or **Certificate information** to display the Certificate Viewer dialog. Select the Details tab, then Bogen CA in the Certificate Hierarchy section.
  - b) On the Safari browser *[MacOS or iOS only]*, select **Show Certificate** in the window that appears.
  - c) As an alternative on Android devices, select the Android system's **Settings > Biometrics and security > Other security settings > View security certificates**, select the **USER** tab, and select the Bogen certificate.
- 4 Verify that the Bogen CA certificate is selected and not the server certificate (the server certificate's name will be an IP address). To verify that the certificate is valid, verify that the displayed fingerprint values match the following:

**SHA-1:** 0A 82 48 F6 9D 97 0F 8D D8 55 D0 E0 59 29 72 DA 64 B1 A8 45

**SHA-256:** 6B D0 D5 8D C8 F7 E8 03 9E A3 F1 52 32 1D 9C 5C 58 8B 4E FA DF 03 43 64 34 C2 6C 63 C5 4A AC 46